

Dockge

How to Install Requirements:

Docker 20+ / Podman (Podman only) podman-docker (Debian: apt install podman-docker) OS:
Major Linux distros that can run Docker/Podman such as: ☐ Ubuntu ☐ Debian (Bullseye or newer)
☐ Raspbian (Bullseye or newer) ☐ CentOS ☐ Fedora ☐ ArchLinux ☐ Debian/Raspbian Buster or
lower is not supported ☐ Windows (Will be supported later) Arch: armv7, arm64, amd64 (a.k.a
x86_64) Basic Default Stacks Directory: /opt/stacks Default Port: 5001

Create directories that store your stacks and stores Dockge's stack

```
mkdir -p /opt/stacks /opt/dockge cd /opt/dockge
```

Download the compose.yaml

```
curl https://raw.githubusercontent.com/louislam/dockge/master/compose.yaml --output  
compose.yaml
```

Start the server

```
docker compose up -d
```

If you are using docker- compose V1 or Podman docker-compose up -d

Dockge is now running on <http://localhost:5001>

Advanced If you want to store your stacks in another directory, you can generate your compose.yaml file by using the following URL with custom query strings.

Download your compose.yaml

`curl "https://dockge.kuma.pet/compose.yaml?port=5001&stacksPath=/opt/stacks" --output
compose.yaml port=5001 stacksPath=/opt/stacks` Interactive compose.yaml generator is available
on: <https://dockge.kuma.pet>

How to Update `cd /opt/dockge docker compose pull && docker compose up -d`

Revision #2

Created 22 July 2024 12:02:13 by CoreStream Group

Updated 22 July 2024 12:03:36 by CoreStream Group