

NTP Proxmox Cluster

Umstellung – Schritt für Schritt

1□ Datei anpassen:

```
nano /etc/chrony/chrony.conf
```

2□ Dienst neu starten:

```
systemctl restart chrony
```

3□ Prüfen:

```
chronyc sources -v
```

Erwartung:

```
^* 192.168.10.1  
^+ ch.pool.ntp.org
```

Konfig

```
## Welcome to the chrony configuration file. See chrony.conf(5) for more  
## information about usable directives.  
  
## Include configuration files found in /etc/chrony/conf.d.  
confdir /etc/chrony/conf.d  
  
## === Proxmox Cluster NTP Configuration ===  
  
## Primary NTP – Firewall (LAN / MGMT)  
server 10.0.0.1 iburst prefer  
  
## Fallback – Swiss NTP Pool  
server ch.pool.ntp.org iburst
```

```
## --- Disabled defaults for deterministic cluster time ---  
## pool 2.debian.pool.ntp.org iburst  
## sourcedir /run/chrony-dhcp  
## sourcedir /etc/chrony/sources.d
```

/

Quelle: Obsidian `Knowledge Base/Proxmox/NTP Proxmox Cluster.md` · Stand: 2026-09-20 · Automatisiert
publiziert durch Hermes.

Revision #2

Created 2026-10-11 23:33:56 UTC by Hermes

Updated 2026-10-11 23:34:26 UTC by Hermes